Wyciąg z listy wniosków o zawieszenia cła na towary dla przemysłu elektronicznego, telekomunikacyjnego i motoryzacyjnego w części dotyczącej elektroniki – lipiec 2023 r..

CYCLE 2023-07

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Working Number	Description	QUOTAS	New or amendment request	Partner Position Country		Public Comments
8414 30 81		1097/2007TR	3017	Rotary type compressor, consisting of a single phase or three phase motor with a cooling capacity range between 2Kw to 8Kw, using a refrigerant fluid of type R32 or R410, for use in the manufacture of air conditioning machines ⁽¹⁾	Q/2000000pieces, 01.01-31.12	Amendment	TR	Applicant	Round 2023-07 - Roll-over request for increase.// Round 2023-01- Request for increase (TR national quota)/ REJECTED Round 2020-07 - Request for increase (TR national quota)/ Round 2019-07 - Request for amendment (TR national quota)

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
3920 62 19		6707528/2022	2039	 Non-transparent poly (ethylene terephthalate) film Coated on both sides with polyvinylidene difluoride / Polyvinyl fluoride based on fluorinated polymer composites 25 µm thick but not more than 27.5 µm and inner (core) PET 250 µm thick but not more than 275 µm With peel strength equal to or greater than 60N/1.5 cm (as determined by ASTM D-903) With a tensile strength equal to or greater than 10000 N/cm2 (100MPa) (as determined by the ASTM D-882method With a total thickness of 300 µm or more but not more than 320 µm, With 1036 mm or more but not more than 1040 mm 	S	New	TR	Applicant	Product for renewable energy industry
8414 90 00		6708104/2022	2800	 Fan assy made of aluminium and magnesium alloy: with an outer diameter 54 mm or more but not more than 130 mm, with a height of 8 mm or more but not more than 30 mm, two discs connected by blades of involute shape, with or without dowel, and with or without washer 	S	New	SI	Applicant	Parts for motor manufacture
8501 32 00		7080081/2022	1702	FUEL CELL MODULE. The module has a PEM fuel cell with a DC/DC converter with an output between 60/80 kW in a voltage range of 400 to 750 VIt also contains an air compressor, a water pump, and a hydrogen pump. Hydrogen tank and high voltage battery are not included. 850132 Of an output exceeding 750 W but not exceeding 75 kWElectric motors and generators (excluding generating sets) - Toyota fuel cell module is a DC Generator, exceeding 750 W, but not exceeding 75kW, not Aircraft	S	New	BE EU	Applicant Opposed	Round 2023-07: battery related product

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
8501 33 00		7079843/2022	1701	FUEL CELL MODULE The module has a PEM fuel cell with a DC/DC converter with an output between 60/80 kW in a voltage range of 400 to 750 V It also contains an air compressor, a water pump, and a hydrogen pump. Hydrogen tank and high voltage battery are not included. 850133 Of an output exceeding 75 kW but not exceeding 375 kW Electric motors and generators (excluding generating sets) - Toyota fuel cell module is a DC Generator, exceeding 75 kW, not exceeding 375 kW Not Aircraft, not drive motor for motor vehicle, not AC or DC motor	S	New	BE EU	Applicant Opposed	Round 2023-07: battery related
8505 11 00		6620328/2022	2034	 Two magnets in a rectangular steel holder with an outer casing of rubber with outer dimensions: a length of 200 mm or more but not more than 205 mm a width of 58 mm or more but not more than 62 mm a height of 25 or more but not more than 30 with a stud mounted in the middle 	S	New	DK	Applicant	Parts for renewable energy sector

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 8505 19 10 2	20	2200205/2019	3010	 SL (12.09.2022) request for removal of the enduse requirement: Arc segments of permanent magnets of agglomerated ferrite, with: a length of 16,8 mm or more, but not more than 110,2 mm, a width of 14,8 mm or more, but not more than 75,2 mm, and a thickness of 4,8 mm or more, but not more than 13,2 mm Current text: Arc segments of permanent magnets of agglomerated ferrite, with: a length of 16,8 mm or more, but not more than 75,2 mm, and a thickness of 4,8 mm or more, but not more than 13,2 mm Current text: Arc segments of permanent magnets of agglomerated ferrite, with: a length of 16,8 mm or more, but not more than 110,2 mm, a width of 14,8 mm or more, but not more than 75,2 mm, a thickness of 4,8 mm or more, but not more than 75,2 mm, 	S	Amendment	SI	Applicant	Round 2023-07: request for amendment./ Round 2020-01 meant to be installed on rotor of electromotor that is used in applications in ventilation and air-conditioning systems

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 8507 60 00	33	1232310/2015	3003	 NL(14.09.2022) request for amendment: Lithium-ion accumulator, with: a length of 150 mm or more, but not more than 1 310 mm, a width of 100 mm or more, but not more than 1 000 mm, a height of 200 mm or more, but not more than 1 500 mm, a weight of 75 kg or more, but not more than 200 kg, a nominal capacity not less than 58 Ah and not more than 500 Ah a nominal output voltage of 230V AC (line to neutral) or a nominal voltage of 50V (± 10 %) Current text: Lithium-ion accumulator, with: a length of 150 mm or more, but not more than 1,000 mm, a width of 100 mm or more, but not more than 1,000 mm, a height of 200 mm or more, but not more than 1,500 mm, a height of 75 kg or more, but not more than 1,500 mm, a nominal capacity not less than 150Ah and not more than 500 Ah, a nominal output voltage of 230V AC (Line to neutral) or a nominal voltage of 230V AC (Line to neutral) or a nominal voltage of 230V AC (Line to neutral) or a nominal voltage of 230V AC (Line to neutral) or a nominal voltage of 230V AC (Line to neutral) or a nominal voltage of 240V AC (Line to neutral) or a nominal voltage of 240V AC (Line to neutral) or a nominal voltage of 64V (±10 %) 	S	Amendment	NL EU	Applicant Opposed	Round 2023-07:request for amendment. Round 2023-01 - review of the suspension Round 2022-01: review of the measure. Round 2020-07 - Objection- withdrawn. Round 2020-01- Amendment - duty rate set to 1,3%. ROUND 07/2019: request for amendment ROUND 01-2016 The product is a battery pack for use in a stationary energy storage application.

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 8536 49 00	50	1940311/2019	3001	 TR(14.09.2022) request for amendment: Relay in the shape of a cube with: a coil operating voltage of 12 VDC or more, but not more than 24 VDC, a contact current carrying capacity of 5A or more, but not more than 15A, a contact voltage of 80 VAC or more, but not more than 270 VAC outer dimensions of 19 mm (± 0,4 mm) X 15,2 mm (± 0,4 mm) X 15,5 mm(± 0,4 mm) for use in the production of control board of white goods Current text: Relay with: a contact current carrying capacity of 5 A or more but not more than 15 A, a nominal voltage of 80 V or more but not more than 270 V, and outer dimensions of 19 mm x 15,2 mm x 15,5 mm, for use in the manufacture of control boards for household appliances⁽¹⁾ 	S	Amendment	TR	Applicant	Round 2023-07- requests for amendment. Round 2020-01 for use in the production of control boards of white goods

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 8537 10 98	50	3033461/2014 PROLONG 2020	3011	 SK(12.09.2023) request for amendment: Electronic control unit (BCM (Body Control Module, IBU (Integrated Body Control Module), or similar): comprising at least: plastic box with printed circuit board whether or not with metal holder, with voltage of 9 VDC or more, but not more than 16 VDC (direct current voltage), able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, of a kind used in the manufacture of goods of Chapter 87 Current text: Electronic control unit BCM (Body Control Module) comprising plastic box with printed circuit board and metal holder, with voltage of 9V or more, but not more than 16V, able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, of a kind used of 9V or more, but not more than 16V, able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder of a kind used in the manufacture of goods of Chapter 87 	S	Amendment	SK	Applicant	Round 2023-07- Request for amendment./ Prolongation Exercise 2020-01-01/ Round 2017-01 :CN change 8537 10 99 50 -> 8537 10 98 50 ROUND 2015-07 Electronic control unit will be placed in the dashboard of a car.

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 8540 91 00	20	4610399/2017 PROLONG 2023	3007	 AT(13.09.2022) request for amendment: Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), with or without a metal housing with electric connectors having a graphite carbon shield mounted in a mini- Vogel type system, separate pyrolytic carbon blocks used as heating elements, and a cathode temperature of less than 1 800 K at a filament current of 1,26 A Current text: Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), in a metal housing with electric connectors having a graphite carbon shield mounted in a mini- Vogel type system separate pyrolytic carbon blocks used as heating elements and a cathode temperature of less than 1800 K at a filament current of 1,26 A 	S	Amendment	AT	Applicant	Round 2023-07; request for amendment./ Prolongation Exercise 2023-01-01 ROUND 2018-07 for incorporation into a cathode ray tube for raster electron microscopes, semiconductor inspection systems or electron beam lithography devices.

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Partner Position Country	Partner Position	Public Comments
ex 9002 11 00	23	1794993/2020	3000	 DE(15.09.2023): Lens with: motorized focus, zoom, aperture, electronically switchable infrared cut filter, an adjustable focal length not less than 2,7 mm and not more than 55mm, a weight of not more than 120 g, a length of less than 70 mm, a diameter of not more than 70 mm Current text Lenses with: motorized focus, zoom, aperture, electronically switchable infrared cut filter, an adjustable focal length not less than 2,7 mm and not more than 55 mm, a weight of not more than 100 g, a length of less than 70 mm, a diameter of not more than 100 g, a length of less than 70 mm, 	S	Amendment	DE	Applicant	Round 2023-07 - request for amendment./ Round 2021-01 Intended use: assembly in cctv cameras.

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)